## NSN 5945-01-271-7454

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-271-7454

| Overall Length:   |
|---|
| 1.156 inches  |
| Overall Height:   |
| 0.485 inches  |
| Overall Width:  |
| 0.895 inches  |
| Case Material:  |
| Plastic   |
| Fragility Factor:   |
| Moderately rugged   |
| Contact Material:   |
| Rhodium   |
| End Application:  |
| Rcvr/xmtr, rad  |
| Winding Quantity:   |
| 1   |
| Purpose For Which Designed:   |
| General   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:   |
| 500.0 ohms single winding   |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:  |
| 1 plug-in terminal single mounting facility   |
| Storage Type:   |
| General purpose warehouse   |
| Features Provided:  |
| Polarized   |
| Cubic Measure:  |
| 0.502 cubic inches  |
| Nonpile-up Main Contact Arrangement:  |
| 1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp:   |
| 12.0 volts dc 25 degrees celsius single winding   |
| Main Contact Load Current Rating At Maximum Rated Voltage:  |
| 100.0 milliamperes dc resistive load  |
| Main Contact Maximum Voltage Rating In Volts:   |
| 100.0 dc  |
| Energizing Element Power Rating:  |

10.0 watts

## NSN 5945-01-271-7454

Reed Relay - Page 2 of 2



| <b>Precious Material And Location:</b> |
|--|
| Contacts rhodium                       |
| Precious Material:                     |
| Rhodium                                |
| Terminal Type And Quantity:            |
| 6 pin all functions                    |
| Shelf Life:                            |
| N/a                                    |
| Unit Of Measure:                       |
|  |
| Demilitarization:                      |
| No                                     |

**Fiig:** A03300