NSN 5945-01-272-3555

Electromagnetic Relay - Page 1 of 2

27.0 amperes ac resistive load



View Online at https://aerobasegroup.com/nsn/5945-01-272-3555

| Overall Length: |
|--|
| Overall Length: |
| 6.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.125 inches single mounting facility |
| Overall Height: |
| 10.000 inches |
| Overall Width: |
| 5.281 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.201 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| End Application: |
| B-1b trainer |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 316.860 cubic inches |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, single throw, normally open, momentary action |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 8.125 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 230.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |

NSN 5945-01-272-3555

Electromagnetic Relay - Page 2 of 2



| Main Contact Maximum | Voltage | Rating In | Volts: |
|----------------------|---------|-----------|--------|
| 600.0 ac | | | |

Terminal Type And Quantity:

6 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300