NSN 5945-01-273-5303

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-273-5303

Overall Length:
0.370 inches
Overall Height:
0.400 inches
Overall Width:
0.370 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
800.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 terminal single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Cubic Measure:
0.055 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.0075 seconds fixed release time
Operating Voltage Rating And Type At Specificationified Temp:
12.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

NSN 5945-01-273-5303

Electromagnetic Relay - Page 2 of 2

No Fiig: A03300



Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Energizing Element Power Rating:
60.0 milliwatts
Special Features:
Failure rate level 0.1 percent
Test Data Document:
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 wire lead all functions
Specification Data:
81349-mil-r-39016/41 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: