NSN 5945-01-274-6410

Electromagnetic Relay - Page 1 of 2

0.625 inches single mounting facility

Overall Length: 1.718 inches

Overall Height: 1.290 inches Overall Width: 1.025 inches



View Online at https://aerobasegroup.com/nsn/5945-01-274-6410

Center To Center Distance Between Mounting Facilities Parallel To Width:

Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
2
Winding Dc Resistance Rating:
405.0 ohms all windings
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized and latching contacts
Cubic Measure:
2.272 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary
Operating Current Rating And Type:
75.0 milliamperes dc all windings

NSN 5945-01-274-6410

Electromagnetic Relay - Page 2 of 2



Time Delay:

0.015 seconds fixed operate time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches single mounting facility and 1.446 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

16 pin all functions

Specification Data:

81349-mil-r-6106/51 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-prf-83536 spec.