NSN 5945-01-274-6533

Electromagnetic Relay - Page 1 of 2

24.0 volts ac 25 degrees celsius single winding



View Online at https://aerobasegroup.com/nsn/5945-01-274-6533

Overall Length:					
4.960 inches					
Center To Center Distance Between Mounting Facilities Parallel To Width:					
1.570 inches single mounting facility					
Overall Height:					
5.590 inches					
Overall Width:					
2.950 inches					
Case Material:					
Plastic					
Unthreaded Mounting Hole Diameter:					
0.157 inches single mounting facility					
Fragility Factor:					
Moderately rugged					
End Application:					
Tactical tss					
Frequency In Hertz:					
60.0					
Winding Quantity:					
1					
Purpose For Which Designed:					
General					
Coil Quantity:					
1					
Duty Type:					
Continuous					
Arc Quenching Method:					
Air					
Mounting Facility Type And Quantity:					
3 unthreaded hole single mounting facility					
Storage Type:					
General purpose warehouse					
Cubic Measure:					
81.793 cubic inches					
Mounting Facility Pattern:					
Triangle single mounting facility					
Nonpile-up Main Contact Arrangement:					
3 pole, single throw, normally open, momentary action					
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:					
3.940 inches single mounting facility					
Operating Voltage Rating And Type At Specificationified Temp:					

NSN 5945-01-274-6533

Electromagnetic Relay - Page 2 of 2



Main	Contact	Load Current	Rating A	At Mavimum	Rated Voltage:
wam	Contact	Load Current	Rating A	At Waxiiiiuiii	Rated voltage.

70.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

600.0 ac

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300