NSN 5945-01-275-2961

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-275-2961

Overall Length:
1.640 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.400 inches single mounting facility
Overall Height:
1.492 inches
Overall Width:
0.802 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.119 inches single mounting facility and 0.122 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
6130-01-150-0762
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
Coil Quantity:
•
1
1 Winding Dc Resistance Rating:
1 Winding Dc Resistance Rating: 500.0 ohms single winding
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type:
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity:
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Cubic Measure:
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Cubic Measure: 1.962 cubic inches
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Cubic Measure: 1.962 cubic inches Mounting Facility Pattern:
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Cubic Measure: 1.962 cubic inches Mounting Facility Pattern: In-line single mounting facility
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Cubic Measure: 1.962 cubic inches Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement:
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Cubic Measure: 1.962 cubic inches Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 3 pole, double throw, one position momentary
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Cubic Measure: 1.962 cubic inches Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement:

12.0 volts dc 25 degrees celsius single winding

NSN 5945-01-275-2961

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Terminal Type And Quantity:

11 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300