## NSN 5945-01-276-2304

Electromagnetic Relay - Page 1 of 2

0.625 inches single mounting facility

Overall Length: 2.230 inches

**Overall Height:** 



View Online at https://aerobasegroup.com/nsn/5945-01-276-2304

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.870 inches
Overall Width:
1.310 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
E2b/c-dcn
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
Winding Dc Resistance Rating: 320.0 ohms single winding
320.0 ohms single winding
320.0 ohms single winding  Duty Type:
320.0 ohms single winding  Duty Type:  Continuous
320.0 ohms single winding  Duty Type:  Continuous  Arc Quenching Method:
320.0 ohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air
320.0 ohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air  Mounting Facility Type And Quantity:
320.0 ohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air  Mounting Facility Type And Quantity:  3 slotted hole single mounting facility
320.0 ohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air  Mounting Facility Type And Quantity:  3 slotted hole single mounting facility  Storage Type:
320.0 ohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air  Mounting Facility Type And Quantity:  3 slotted hole single mounting facility  Storage Type:  General purpose warehouse
320.0 ohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air  Mounting Facility Type And Quantity:  3 slotted hole single mounting facility  Storage Type:  General purpose warehouse  Features Provided:
320.0 ohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 3 slotted hole single mounting facility  Storage Type: General purpose warehouse  Features Provided: Polarized
320.0 ohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 3 slotted hole single mounting facility  Storage Type: General purpose warehouse  Features Provided: Polarized  Cubic Measure:
320.0 ohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 3 slotted hole single mounting facility  Storage Type: General purpose warehouse  Features Provided: Polarized  Cubic Measure: 5.463 cubic inches
320.0 ohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 3 slotted hole single mounting facility  Storage Type: General purpose warehouse  Features Provided: Polarized  Cubic Measure: 5.463 cubic inches  Mounting Facility Pattern:
320.0 ohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 3 slotted hole single mounting facility  Storage Type: General purpose warehouse  Features Provided: Polarized  Cubic Measure: 5.463 cubic inches  Mounting Facility Pattern:  Triangle single mounting facility

## NSN 5945-01-276-2304

Electromagnetic Relay - Page 2 of 2



## Time Delay:

160.00 seconds fixed operate time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:** 

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

8 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300