## NSN 5945-01-276-2311

Electromagnetic Relay - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5945-01-276-2311

| 2b single mounting facility   |  |  |  |  |
|---|--|--|--|--|
| Thread Direction:   |  |  |  |  |
| Right-hand single mounting facility                                       |  |  |  |  |
| Overall Length:   |  |  |  |  |
| 3.125 inches  |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |  |  |  |  |
| 1.375 inches single mounting facility                                     |  |  |  |  |
| Overall Height:   |  |  |  |  |
| 2.844 inches  |  |  |  |  |
| Overall Width:  |  |  |  |  |
| 1.031 inches  |  |  |  |  |
| Case Material:  |  |  |  |  |
| Plastic   |  |  |  |  |
| Environmental Protection:   |  |  |  |  |
| Dustproof   |  |  |  |  |
| Fragility Factor:   |  |  |  |  |
| Moderately rugged   |  |  |  |  |
| End Application:  |  |  |  |  |
| 5895-00-936-5510  |  |  |  |  |
| Winding Quantity:   |  |  |  |  |
| 1   |  |  |  |  |
| Purpose For Which Designed:   |  |  |  |  |
| General   |  |  |  |  |
| Coil Quantity:  |  |  |  |  |
| 1   |  |  |  |  |
| Duty Type:  |  |  |  |  |
| Continuous  |  |  |  |  |
| Arc Quenching Method:   |  |  |  |  |
| Air   |  |  |  |  |
| Mounting Facility Type And Quantity:                                      |  |  |  |  |
| 2 threaded hole single mounting facility                                  |  |  |  |  |
| Pile-up Main Contact Form Arrangement:                                    |  |  |  |  |
| 24a   |  |  |  |  |
| Storage Type:   |  |  |  |  |
| General purpose warehouse   |  |  |  |  |
| Cubic Measure:  |  |  |  |  |
| 9.163 cubic inches  |  |  |  |  |
| Thready Qty Per Inch (tpi):   |  |  |  |  |
| 48 single mounting facility   |  |  |  |  |
| Thread Size:  |  |  |  |  |
| 0.099 inches single mounting facility                                     |  |  |  |  |

## NSN 5945-01-276-2311

Electromagnetic Relay - Page 2 of 2



| VI | ounting | <b>Facility</b> | Pattern: |
|----|---------|-----------------|----------|
|----|---------|-----------------|----------|

In-line single mounting facility

Time Delay:

0.015 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

125.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

50 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300