## NSN 5945-01-277-8034

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-277-8034

Overa	II I	en	ath:
Overa		.cii	uui.

Between 1.698 inches and 1.718 inches

## **Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Overall Height:** 

Between 0.505 inches and 0.525 inches

Overall Width:

Between 1.290 inches and 1.320 inches

**Mounting Slot Width:** 

0.150 inches single mounting facility

**Case Material:** 

Metal

**Environmental Protection:** 

Hermetic

**Fragility Factor:** 

Moderately rugged

**End Application:** 

Camera, motion

**Winding Quantity:** 

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

Winding Dc Resistance Rating:

320.0 ohms single winding

**Duty Type:** 

Continuous

**Arc Quenching Method:** 

Air

**Mounting Facility Type And Quantity:** 

2 slotted hole single mounting facility

**Storage Type:** 

General purpose warehouse

**Features Provided:** 

Polarized

**Cubic Measure:** 

1.191 cubic inches

**Mounting Facility Pattern:** 

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:** 

2 pole, double throw, one position momentary

## NSN 5945-01-277-8034

Electromagnetic Relay - Page 2 of 2



## **Operating Current Rating And Type:**

110.0 milliamperes dc single winding

Time Delay:

0.01 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:** 

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

8 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300