NSN 5945-01-277-8546

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-277-8546

Overall Length:

Between 1.880 inches and 1.900 inches

Overall Diameter:

Between 1.120 inches and 1.140 inches

Case Material:

Metal

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.141 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

5985-01-267-8234

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

290.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

1.939 cubic inches

Mounting Facility Pattern:

Ciruclar single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Time Delay:

0.01 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes ac resistive load and 12.0 amperes dc resistive load

NSN 5945-01-277-8546

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

3600.0 ac and 3600.0 dc

Test Data Document:

81349-mil-r-83726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug contacts

Specification Data:

81349-mil-r-83725/12 government specification

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300