NSN 5945-01-278-7093

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-278-7093

Overall Length:
3.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.125 inches single mounting facility
Overall Height:
4.550 inches
Overall Width:
3.570 inches
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.188 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.938 inches single mounting facility
Fragility Factor:
Moderately rugged
Frequency In Hertz:
Between 50.0 and 60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
•
1
1 Winding Dc Resistance Rating:
Winding Dc Resistance Rating:
Winding Dc Resistance Rating: 631.6 ohms single winding
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type:
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type: Continuous
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity:
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Storage Type:
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Storage Type: General purpose warehouse
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Storage Type: General purpose warehouse Mounting Facility Pattern:
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Storage Type: General purpose warehouse Mounting Facility Pattern: Rectangular single mounting facility
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Storage Type: General purpose warehouse Mounting Facility Pattern: Rectangular single mounting facility Nonpile-up Main Contact Arrangement:
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Storage Type: General purpose warehouse Mounting Facility Pattern: Rectangular single mounting facility Nonpile-up Main Contact Arrangement: 3 pole, single throw, normally open, momentary action
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Storage Type: General purpose warehouse Mounting Facility Pattern: Rectangular single mounting facility Nonpile-up Main Contact Arrangement: 3 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp:
Winding Dc Resistance Rating: 631.6 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Storage Type: General purpose warehouse Mounting Facility Pattern: Rectangular single mounting facility Nonpile-up Main Contact Arrangement: 3 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 120.0 volts ac 25 degrees celsius single winding

480.0 ac

NSN 5945-01-278-7093

Electromagnetic Relay - Page 2 of 2



Terminal T	ype And	Quantity:
------------	---------	-----------

6 tab w/screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300