

View Online at <https://aerobasegroup.com/nsn/5945-01-281-6931>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

Between 1.990 inches and 2.010 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility

Overall Height:

Between 4.938 inches and 5.000 inches

Overall Width:

Between 1.750 inches and 1.813 inches

Case Material:

Plastic

Environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Height:

4.402 inches single mounting facility

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Gold

End Application:

Bsy1 fy88

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Pile-up Main Contact Form Arrangement:

11c

Storage Type:

General purpose warehouse

Cubic Measure:

18.221 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Time Delay:

0.015 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Terminal surfaces and contacts silver and contact surfaces gold

Precious Material:

Gold and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

35 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300