## NSN 5945-01-282-2773

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-282-2773 **Overall Length:** 0.562 inches **Overall Diameter:** 0.370 inches **Environmental Protection:** Hermetic and shock resistant and vibration resistant and corrosion resistant Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 1.025 kilohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 5 terminal single mounting facility **Nonpile-up Main Contact Arrangement:** 1 pole, double throw, one position momentary Time Delay: 0.004 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc **Test Data Document:** 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 5 wire lead all functions **Specification Data:** 81349-mil-r-39016/10 government specification Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A03300