

View Online at <https://aerobasegroup.com/nsn/5945-01-282-7830>

**Overall Length:**

1.718 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.615 inches single mounting facility and 0.635 inches single mounting facility

**Overall Height:**

1.010 inches

**Overall Width:**

1.025 inches

**Mounting Slot Width:**

0.140 inches single mounting facility and 0.160 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**Contact Surface Treatment:**

Tin plated

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 slotted hole single mounting facility

**Cubic Measure:**

1.779 cubic inches

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, double throw, one position momentary

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.436 inches single mounting facility and 1.456 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

12.0 amperes dc inductive load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

11 pin all functions

**Specification Data:**

96906-ms27743 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-r-6106 spec.