

View Online at <https://aerobasegroup.com/nsn/5945-01-283-0617>

Overall Length:

1.718 inches

Overall Height:

1.010 inches

Overall Width:

1.025 inches

Mounting Slot Width:

0.150 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Nonpile-up Auxiliary Contact Arrangement:

1 pole, double throw, two positions momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.446 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac inductive load and 12.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac lamp load and 500.0 milliamperes dc lamp load

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

11 pin all functions

Specification Data:

81349-mil-r-6106/13 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300