# NSN 5945-01-283-4417

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-283-4417

## **Overall Length:**

1.719 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.437 inches single mounting facility

## **Overall Height:**

1.750 inches

## **Overall Width:**

1.188 inches

## **Case Material:**

Metal

## **Environmental Protection:**

Hermetic

## Unthreaded Mounting Hole Diameter:

0.156 inches single mounting facility

## Fragility Factor:

## Moderately rugged

Winding Quantity:

1

### Purpose For Which Designed:

General

#### **Coil Quantity:**

1

## Winding Dc Resistance Rating:

475.0 ohms single winding

#### Duty Type:

Continuous

#### Arc Quenching Method:

Air

#### Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

#### Storage Type:

General purpose warehouse

#### **Cubic Measure:**

3.574 cubic inches

#### **Mounting Facility Pattern:**

In-line single mounting facility

#### Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

#### Time Delay:

0.012 seconds fixed operate time

#### Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-283-4417

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 30.0 dc

Terminal Type And Quantity:

14 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300