# NSN 5945-01-283-6902

Electromagnetic Relay - Page 1 of 2

Between 0.350 inches and 0.370 inches

**Overall Length:** 

115.0 ac and 28.0 dc



View Online at https://aerobasegroup.com/nsn/5945-01-283-6902

Overall Height:
Between 0.378 inches and 0.398 inches
Overall Width:
Between 0.350 inches and 0.370 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
2.0 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.054 cubic inches
Nonpile-up Main Contact Arrangement:
1 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.004 seconds fixed release time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
100.0 milliamperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:

## NSN 5945-01-283-6902

Electromagnetic Relay - Page 2 of 2



Special	Features:
---------	-----------

Failure rate level 0.1 percent

#### **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

5 wire lead all functions

### **Specification Data:**

81349-mil-r-39016/23 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300