NSN 5945-01-284-2844

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-284-2844

Overall	Length:
---------	---------

Between 2.730 inches and 2.780 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

Between 1.720 inches and 1.780 inches

Overall Width:

Between 1.160 inches and 1.220 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.177 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized

Cubic Measure:

6.037 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

300.0 milliamperes dc single winding

NSN 5945-01-284-2844

Electromagnetic Relay - Page 2 of 2



	Time	De	lay:
--	------	----	------

5.00 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300