# NSN 5945-01-284-2844

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-284-2844

### **Overall Length:**

Between 2.730 inches and 2.780 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches single mounting facility

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

#### **Overall Height:**

Between 1.720 inches and 1.780 inches

#### **Overall Width:**

Between 1.160 inches and 1.220 inches

#### Case Material:

Metal

**Environmental Protection:** 

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.177 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

## Winding Quantity:

1

### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

## Duty Type:

Continuous

## Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## **Features Provided:**

Polarized

## Cubic Measure:

6.037 cubic inches

## Mounting Facility Pattern:

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

## Operating Current Rating And Type:

300.0 milliamperes dc single winding

# NSN 5945-01-284-2844

Electromagnetic Relay - Page 2 of 2



**Time Delay:** 

5.00 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300