NSN 5945-01-286-2145

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-286-2145

Overall Length:

Between 1.708 inches and 1.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.436 inches single mounting facility and 1.446 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.615 inches single mounting facility and 0.625 inches single mounting facility

Overall Height:

Between 1.000 inches and 1.010 inches

Overall Width:

Between 1.015 inches and 1.025 inches

Mounting Slot Width:

0.140 inches single mounting facility and 0.150 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

End Application:

B-1b aircraft

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

1.776 cubic inches

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Time Delay:

15.00 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches single mounting facility and 1.416 inches single mounting facility

NSN 5945-01-286-2145

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac inductive load and 12.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Terminal Type And Quantity:

9 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300