## NSN 5945-01-286-3621

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-286-3621

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
0.937 inches
Overall Height:
1.187 inches
Overall Width:
0.735 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
Winding Dc Resistance Rating:
Winding Dc Resistance Rating: 500.0 ohms single winding
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type:
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method:
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity:
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Pile-up Main Contact Form Arrangement:
Winding Dc Resistance Rating: 500.0 ohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 1 threaded stud single mounting facility  Pile-up Main Contact Form Arrangement: 2c
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 2c Storage Type:
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 2c Storage Type: General purpose warehouse
Winding Dc Resistance Rating: 500.0 ohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 1 threaded stud single mounting facility  Pile-up Main Contact Form Arrangement: 2c  Storage Type: General purpose warehouse  Cubic Measure:
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 2c Storage Type: General purpose warehouse Cubic Measure: 0.817 cubic inches
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 2c Storage Type: General purpose warehouse Cubic Measure: 0.817 cubic inches Thready Qty Per Inch (tpi):
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 2c Storage Type: General purpose warehouse Cubic Measure: 0.817 cubic inches Thready Qty Per Inch (tpi): 48 single mounting facility
Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 2c Storage Type: General purpose warehouse Cubic Measure: 0.817 cubic inches Thready Qty Per Inch (tpi): 48 single mounting facility Thread Size:

## NSN 5945-01-286-3621

Electromagnetic Relay - Page 2 of 2



## Operating Voltage Rating And Type At Specificationified Temp:

6.0 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 29.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

8 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300