## NSN 5945-01-287-7576

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-287-7576

| Overall Length:   |
|---|
| 1.339 inches  |
| Overall Height:   |
| 2.205 inches  |
| Overall Width:  |
| 1.417 inches  |
| Case Material:  |
| Plastic   |
| Environmental Protection:   |
| Dustproof   |
| Fragility Factor:   |
| Moderately rugged   |
| End Application:  |
| 4920-01-224-8880 test stand, electric and hydraulic system components |
| Winding Quantity:   |
| 1   |
| Purpose For Which Designed:   |
| General   |
| Coil Quantity:  |
| 1   |
| Duty Type:  |
| Continuous  |
| Arc Quenching Method:   |
| Air   |
| Mounting Facility Type And Quantity:                                  |
| 1 plug-in terminal single mounting facility                           |
| Storage Type:   |
| General purpose warehouse   |
| Cubic Measure:  |
| 4.184 cubic inches  |
| Nonpile-up Main Contact Arrangement:                                  |
| 2 pole, double throw, one position momentary                          |
| Time Delay:   |
| 0.025 seconds fixed operate and release time                          |
| Operating Voltage Rating And Type At Specificationified Temp:         |
| 115.0 volts ac 25 degrees celsius single winding                      |
| Main Contact Load Current Rating At Maximum Rated Voltage:            |
| 15.0 amperes ac resistive load and 15.0 amperes dc resistive load     |
| Main Contact Maximum Voltage Rating In Volts:                         |
| 125.0 ac and 24.0 dc  |
| Precious Material And Location:                                       |

Contacts silver

## NSN 5945-01-287-7576

Electromagnetic Relay - Page 2 of 2



| Precious | Mate | rial | ŀ |
|----------|------|------|---|
|----------|------|------|---|

Silver

**Terminal Type And Quantity:** 

8 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A03300