NSN 5945-01-288-3815

Electromagnetic Relay - Page 1 of 2

115.0 volts ac 25 degrees celsius single winding



View Online at https://aerobasegroup.com/nsn/5945-01-288-3815

Overell Length.
Overall Length:
4.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.750 inches single mounting facility
Overall Height:
3.188 inches
Overall Width:
3.188 inches
Case Material:
Plastic and metal
Unthreaded Mounting Hole Diameter:
0.164 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Boiler stm au
Frequency In Hertz:
Between 50.0 and 60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
43.194 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
2.125 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:

NSN 5945-01-288-3815

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

16.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300