

View Online at <https://aerobasegroup.com/nsn/5945-01-288-5630>

Overall Length:

2.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility

Overall Height:

3.000 inches

Overall Width:

2.500 inches

Mounting Slot Width:

0.218 inches single mounting facility

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Cadmium plated

End Application:

Shelter, model

Frequency In Hertz:

Between 50.0 and 60.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

20.625 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, double make, momentary action

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

30.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

600.0 ac

Energizing Element Power Rating:

5.0 watts

Special Features:

Reference only: p/n's & cage's 13230e3597, 97403 x 41nb30af, 23826 x p25p42a12p1-120, 77342 army // drawing item name: relay, contactor, definite purpose, 3pst // end item: force provider (used on: 4120-01-413-7835)

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300