NSN 5945-01-288-6245

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-288-6245

view Offilite at https://aerobasegroup.com/hsi//0340-01-200-0240
Overall Length:
Between 0.790 inches and 0.810 inches
Overall Height:
Between 0.620 inches and 0.640 inches
Overall Width:
Between 0.790 inches and 0.810 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
1430-01-191-8780 radar set, semitrailer mounted
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
400.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Cubic Measure:
0.420 cubic inches
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.006 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp

28.0 volts dc 25 degrees celsius single winding

NSN 5945-01-288-6245

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac motor load and 2.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate level 0.3 percent

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

14 pin all functions

Specification Data:

81349-mil-r-6106/28 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300