

View Online at <https://aerobasegroup.com/nsn/5945-01-289-4174>

Overall Length:

1.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.446 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

1.015 inches

Overall Width:

1.000 inches

Mounting Slot Width:

0.150 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

Control unit

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

290.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Time Delay:

0.015 seconds fixed operate and release time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, double throw, two positions momentary

Operating Voltage Rating And Type At Specificationified Temp:

29.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac inductive load and 12.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac lamp load and 500.0 milliamperes dc lamp load

Terminal Type And Quantity:

11 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300