NSN 5945-01-289-4873

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-289-4873

| Overall Length: |
|--|
| 3.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.880 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.750 inches single mounting facility |
| Overall Height: |
| 6.230 inches |
| Overall Width: |
| 3.090 inches |
| Environmental Protection: |
| Dust tight |
| Unthreaded Mounting Hole Diameter: |
| 0.199 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| End Application: |
| Misc. Engin. |
| Frequency In Hertz: |
| Between 50.0 and 60.0 |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 6 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Time Delay: |
| 5.00 seconds adjustable release time and 50.00 seconds adjustable release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 120.0 volts ac 25 degrees celsius single winding |
| |

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac resistive load and 15.0 amperes dc resistive load

NSN 5945-01-289-4873

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300