NSN 5945-01-290-3790

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-290-3790 **Overall Length:** 0.780 inches **Overall Height:** 0.280 inches **Overall Diameter:** 0.370 inches **Environmental Protection:** Hermetic and vibration proof and shock proof Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 390.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 terminal single mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary **Criticality Code Justification:** Spcl **Operating Voltage Rating And Type At Specificationified Temp:** 12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 100.0 milliamperes dc lamp load Main Contact Maximum Voltage Rating In Volts: 28.0 dc **Special Features:** Lead Ig 0.500 in. Min., temp range m 65 degrees c to p 125 degrees c **Special Test Features:** Failure rate level /percent per 10000 cycles/ 0.1 percent **Terminal Type And Quantity:** 8 wire lead all functions **Specification Data:** 81349-mil-r-39016/9 government specification Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5945-01-290-3790

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300