NSN 5945-01-290-6628

Electromagnetic Relay - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5945-01-290-6628

Between 0.785 inches and 0.805 inches
Overall Height:
Between 0.443 inches and 0.463 inches
Overall Width:
Between 0.384 inches and 0.404 inches
Case Material:
Plastic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
End Application:
Mmts loose eq
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
45.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.142 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.005 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
5.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
500.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

NSN 5945-01-290-6628

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300