### NSN 5945-01-291-0734

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-291-0734

Overa	11 1	and	th:
Overa	II ∟	enu	un.

Between 4.510 inches and 4.530 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.990 inches single mounting facility and 4.010 inches single mounting facility

**Overall Height:** 

Between 4.585 inches and 4.625 inches

**Overall Width:** 

Between 2.730 inches and 2.750 inches

**Case Material:** 

Metal

#### **Unthreaded Mounting Hole Diameter:**

0.281 inches single mounting facility and 0.312 inches single mounting facility

**Fragility Factor:** 

Moderately rugged

#### **End Application:**

2350-01-277-5770 howitzer, medium, m-109 series; field artillery ammunition support vehicle (faagy) (m992)

**Winding Quantity:** 

'

#### **Purpose For Which Designed:**

General

**Coil Quantity:** 

CO

# 1 Duty Type:

Continuous

#### **Arc Quenching Method:**

Air

#### **Mounting Facility Type And Quantity:**

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

#### **Mounting Facility Pattern:**

In-line single mounting facility

#### **Criticality Code Justification:**

Feat

#### **Operating Voltage Rating And Type At Specificationified Temp:**

24.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 amperes dc resistive load

#### **Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

#### **Special Features:**

Weapon system essential

## NSN 5945-01-291-0734

Electromagnetic Relay - Page 2 of 2



Terminal Type A	and Quantity	<b>/</b> :
-----------------	--------------	------------

1 connector, receptacle all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300