## NSN 5945-01-291-4025

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-291-4025

#### **Overall Length:**

0.280 inches

**Overall Diameter:** 

0.370 inches

## **Environmental Protection:**

Hermetic and salt spray resistant

## Winding Quantity:

1

## **Coil Quantity:**

1

## Winding Dc Resistance Rating:

1560.0 ohms single winding

**Duty Type:** 

Continuous

## Mounting Facility Type And Quantity:

8 printed circuit terminal single mounting facility

## **Features Provided:**

Coil voltage suppression and polarized

#### **Mounting Facility Pattern:**

Ciruclar single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, two positions momentary

## Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

0.2 amperes dc motor load

#### Angle Between Adjacent Mounting Facilities:

36.0 degrees single mounting facility

#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Test Data Document:

81349--39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

8 wire lead all functions

#### **Specification Data:**

81349--39016-033 government specification

#### Shelf Life:

N/a

- Unit Of Measure:
- --
- Demilitarization:
- No

# NSN 5945-01-291-4025

Electromagnetic Relay - Page 2 of 2

**Fiig:** A03300

