NSN 5945-01-291-7296

Electrical Solenoid - Page 1 of 2

Body Style:Cylindrical frame



View Online at https://aerobasegroup.com/nsn/5945-01-291-7296

Center To Center Distance Between Mounting Facilities Parallel To Width:
1.850 inches
Body Length:
8.100 inches
Case Material:
Steel, corrosion resisting
Unthreaded Mounting Hole Diameter:
0.281 inches
Mounting Base Length:
3.000 inches
Mounting Base Width:
3.000 inches
End Application:
Lantirn mob shelter set
Inclosure Type:
Fully enclosed
Magnetic Coil Quantity:
2
Duty Type:
Continuous
Terminal Location:
Terminal Location:
Top edge
Top edge
Top edge Voltage Rating In Volts:
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity:
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole Torque Rating And Type:
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole Torque Rating And Type: 20.00 inch-pounds starting
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole Torque Rating And Type: 20.00 inch-pounds starting Features Provided:
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole Torque Rating And Type: 20.00 inch-pounds starting Features Provided: Coils connected in parallel
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole Torque Rating And Type: 20.00 inch-pounds starting Features Provided: Coils connected in parallel Actuator Stroke Type:
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole Torque Rating And Type: 20.00 inch-pounds starting Features Provided: Coils connected in parallel Actuator Stroke Type: Push
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole Torque Rating And Type: 20.00 inch-pounds starting Features Provided: Coils connected in parallel Actuator Stroke Type: Push Linear Force Delivered:
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole Torque Rating And Type: 20.00 inch-pounds starting Features Provided: Coils connected in parallel Actuator Stroke Type: Push Linear Force Delivered: 225.00 grams
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole Torque Rating And Type: 20.00 inch-pounds starting Features Provided: Coils connected in parallel Actuator Stroke Type: Push Linear Force Delivered: 225.00 grams Power Takeoff Connection Type:
Top edge Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole Torque Rating And Type: 20.00 inch-pounds starting Features Provided: Coils connected in parallel Actuator Stroke Type: Push Linear Force Delivered: 225.00 grams Power Takeoff Connection Type: Internal plunger
Voltage Rating In Volts: Between 110.0 ac and 130.0 ac Mounting Facility Type And Quantity: 2 threaded hole Torque Rating And Type: 20.00 inch-pounds starting Features Provided: Coils connected in parallel Actuator Stroke Type: Push Linear Force Delivered: 225.00 grams Power Takeoff Connection Type: Internal plunger Mounting Facility Pattern:

NSN 5945-01-291-7296

Electrical Solenoid - Page 2 of 2



Terminal Type And Quantity:
3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A134a0