NSN 5945-01-293-3976

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-293-3976

Overall Length:

Between 3.850 inches and 3.910 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.470 inches single mounting facility and 3.530 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.720 inches single mounting facility and 2.780 inches single mounting facility

Overall Height:

Between 3.780 inches and 3.830 inches

Overall Width:

Between 3.470 inches and 3.530 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.161 inches single mounting facility and 0.181 inches single mounting facility

Fragility Factor:

Moderately delicate

Winding Quantity:

.

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

51.739 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action

Time Delay:

5.00 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

460.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

NSN 5945-01-293-3976

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts: 230.0 ac and 28.0 dc Special Features: 3 phase coil Terminal Type And Quantity:

5 tab w/screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300