NSN 5945-01-293-4063

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-293-4063

| Body Style: |
|---|
| Enclosed frame |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| Between 0.495 inches and 0.505 inches |
| Body Length: |
| 2.217 inches |
| Body Width: |
| 1.655 inches |
| Body Height: |
| 1.468 inches |
| Case Material: |
| Metal |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.500 inches |
| Maximum Operating Temp: |
| 25.0 degrees celsius |
| Fragility Factor: |
| Moderately rugged |
| Actuator Diameter: |
| 0.500 inches |
| End Application: |
| Ant load cart |
| Frequency In Hertz: |
| 60.0 |
| Inclosure Type: |
| Fully enclosed |
| Magnetic Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Terminal Location: |
| End opposite actuator |
| Electric Power Rating: |
| 11.5 watts |
| Voltage Rating In Volts: |
| 120.0 ac |
| Mounting Facility Type And Quantity: |
| 8 threaded hole |
| Current Rating: |
| 240.0 milliamperes |
| Storage Type: |

General purpose warehouse

NSN 5945-01-293-4063

Electrical Solenoid - Page 2 of 2



| Actuator Stroke Type: |
|--------------------------------|
| Pull |
| Power Takeoff Connection Type: |
| Slotted-drilled-tapped |
| Mounting Facility Pattern: |
| Eight position rectangular |
| Terminal Type And Quantity: |
| 2 quick disconnect, male |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A134a0