

View Online at <https://aerobasegroup.com/nsn/5945-01-294-5680>

**Overall Length:**

3.750 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.250 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.750 inches single mounting facility

**Overall Height:**

3.150 inches

**Overall Width:**

2.500 inches

**Mounting Slot Width:**

0.344 inches single mounting facility

**Unthreaded Mounting Hole Diameter:**

0.078 inches single mounting facility

**End Application:**

Asr9

**Frequency In Hertz:**

Between 50.0 and 60.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

1800.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 slotted hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, single throw, normally open, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

250.0 ac

**Operating Voltage Rating And Type At Specificationified Temp:**

120.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

40.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

600.0 ac

**Special Features:**

Function, relay, contactor; reference data, 11k7, ti-6310.30, fa 10082, pg 8-18, westinghouse

**Terminal Type And Quantity:**

2 screw all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300