

View Online at <https://aerobasegroup.com/nsn/5945-01-294-5680>

Overall Length:

3.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility

Overall Height:

3.150 inches

Overall Width:

2.500 inches

Mounting Slot Width:

0.344 inches single mounting facility

Unthreaded Mounting Hole Diameter:

0.078 inches single mounting facility

End Application:

Asr9

Frequency In Hertz:

Between 50.0 and 60.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

1800.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 slotted hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

250.0 ac

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

40.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

600.0 ac

Special Features:

Function, relay, contactor; reference data, 11k7, ti-6310.30, fa 10082, pg 8-18, westinghouse

Terminal Type And Quantity:

2 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300