

View Online at <https://aerobasegroup.com/nsn/5945-01-295-8450>

Overall Length:

Between 0.922 inches and 0.932 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.401 inches single mounting facility and 1.411 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.495 inches single mounting facility and 0.505 inches single mounting facility

Overall Height:

1.300 inches

Overall Width:

Between 0.922 inches and 0.932 inches

Mounting Slot Width:

0.170 inches single mounting facility and 0.180 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

End Application:

Pltd wire mem

Frequency In Hertz:

400.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

16.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

1.129 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.008 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

6.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.5 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

14 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300