NSN 5945-01-296-3495

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-296-3495

| Overall Length: |
|---|
| 75.0 millimeters |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 60.0 millimeters single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 35.0 millimeters single mounting facility |
| Overall Height: |
| 130.0 millimeters |
| Overall Width: |
| 55.0 millimeters |
| Environmental Protection: |
| Shock proof |
| Unthreaded Mounting Hole Diameter: |
| 4.8 millimeters single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| End Application: |
| Panel, power d |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 20.520 cubic inches |
| Mounting Facility Pattern: |
| Diagonal single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 8 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 24.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |

10.0 amperes dc resistive load

NSN 5945-01-296-3495

Electromagnetic Relay - Page 2 of 2



220.0 ac

Terminal Type And Quantity:

10 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300