

View Online at <https://aerobasegroup.com/nsn/5945-01-297-2232>

**Overall Length:**

3.400 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.677 inches single mounting facility and 2.697 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.240 inches single mounting facility and 3.260 inches single mounting facility

**Overall Height:**

Between 1.937 inches and 2.063 inches

**Overall Width:**

2.950 inches

**Case Material:**

Metal

**Environmental Protection:**

Hermetic

**Unthreaded Mounting Hole Diameter:**

0.213 inches single mounting facility and 0.223 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**End Application:**

Serd0014eleca

**Frequency In Hertz:**

400.0

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

20.692 cubic inches

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, momentary action

**Time Delay:**

0.03 seconds fixed operate time

**Nonpile-up Auxiliary Contact Arrangement:**

2 pole, single throw, normally open, momentary action

**Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts ac 25 degrees celsius single winding and 28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

50.0 amperes ac resistive load and 50.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

25.0 probe ac resistive load and 25.0 probe dc resistive load

**Terminal Type And Quantity:**

8 threaded stud all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300