

View Online at <https://aerobasegroup.com/nsn/5945-01-298-1996>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Thread Length:

0.375 inches single mounting facility and 0.406 inches single mounting facility

Overall Length:

2.062 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility

Overall Height:

1.810 inches

Overall Width:

2.062 inches

Environmental Protection:

Hermetic

Winding Quantity:

200

Coil Quantity:

1

Winding Dc Resistance Rating:

56.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Pile-up Main Contact Form Arrangement:

4c

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Operating Current Rating And Type:

0.5 amperes dc single winding

Time Delay:

0.50 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Minimum Differential Electrical Operating Rating:

20.0 volts

Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

12 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300