

View Online at <https://aerobasegroup.com/nsn/5945-01-298-1996>

**Thread Class:**

2a single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Thread Length:**

0.375 inches single mounting facility and 0.406 inches single mounting facility

**Overall Length:**

2.062 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.500 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.500 inches single mounting facility

**Overall Height:**

1.810 inches

**Overall Width:**

2.062 inches

**Environmental Protection:**

Hermetic

**Winding Quantity:**

200

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

56.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 threaded stud single mounting facility

**Pile-up Main Contact Form Arrangement:**

4c

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.138 inches single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Operating Current Rating And Type:**

0.5 amperes dc single winding

**Time Delay:**

0.50 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Minimum Differential Electrical Operating Rating:**

20.0 volts

**Main Contact Load Current Rating At Maximum Rated Voltage:**

500.0 milliamperes dc inductive load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

12 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300