NSN 5945-01-299-3284

Electromagnetic Relay - Page 1 of 2

24.0 volts ac 25 degrees celsius single winding



View Online at https://aerobasegroup.com/nsn/5945-01-299-3284

Overall Length:
3.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.750 inches single mounting facility
Overall Height:
5.250 inches
Overall Width:
2.375 inches
Mounting Slot Width:
0.190 inches single mounting facility
Unthreaded Mounting Hole Diameter:
0.190 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Washer-extr d
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility and 1 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
43.640 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
8 pole, single throw, normally open, momentary action
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
3.125 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:

NSN 5945-01-299-3284

Electromagnetic Relay - Page 2 of 2



Main (Contact	Load	Curront	Dating	۸.	Maximum	Datad	Valtage:
IVIAIII (Joniaci	Loau	Current	Rauny	Αι	Maximum	Raieu	voitage.

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

600.0 ac

Terminal Type And Quantity:

18 screw all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300