## NSN 5945-01-299-6288

Electromagnetic Relay - Page 1 of 2

75.0 millimeters single mounting facility

35.0 millimeters single mounting facility

Overall Length: 85.0 millimeters

Overall Height: 107.0 millimeters Overall Width: 45.0 millimeters



View Online at https://aerobasegroup.com/nsn/5945-01-299-6288

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

Center To Center Distance Between Mounting Facilities Parallel To Width:

Unthreaded Mounting Hole Diameter:  4.8 millimeters single mounting facility  Fragility Factor:  Moderately rugged  End Application:
4.8 millimeters single mounting facility  Fragility Factor:  Moderately rugged  End Application:
Fragility Factor:  Moderately rugged  End Application:
Moderately rugged End Application:
End Application:
• •
0.711
Switchboard
Frequency In Hertz:
Between 50.0 and 60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Mounting Facility Pattern:
Diagonal single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, momentary action
Operating Voltage Rating And Type At Specificationified Temp
440.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
16.0 amperes ac resistive load
Main Contact Maximum Voltage Rating In Volts:
380.0 ac

## NSN 5945-01-299-6288

Electromagnetic Relay - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

16 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300