

View Online at <https://aerobasegroup.com/nsn/5945-01-300-8955>

**Overall Length:**

1.062 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.850 inches single mounting facility

**Overall Height:**

0.320 inches

**Overall Width:**

0.310 inches

**Unthreaded Mounting Hole Diameter:**

0.091 inches single mounting facility

**End Application:**

Scadc compute

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

0.05 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

2 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Criticality Code Justification:**

Feat

**Time Delay:**

0.004 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:**

18.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

100.0 milliamperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Special Features:**

One percent failure rate

**Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 wire hook all functions

**Specification Data:**

81349-mil-r-39016/13 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300