## NSN 5945-01-301-9788

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-301-9788

Overall Length:
1.025 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.615 inches single mounting facility and 0.635 inches single mounting facility
Overall Height:
1.010 inches
Overall Width:
1.025 inches
Mounting Slot Width:
0.140 inches single mounting facility and 0.160 inches single mounting facility
Environmental Protection:
Hermetic and shock resistant and vibration resistant and water resistant
Fragility Factor:
Moderately rugged
End Application:
F-14a-dcn
Frequency In Hertz:
400.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
1.061 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
30.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

## NSN 5945-01-301-9788

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum	Voltage	Rating	In	Volts:
200 0 ac and 28 0 dc				

200.0 ac and 28.0 dc

**Special Features:** 

Relay has a repeat cycle timer

**Terminal Type And Quantity:** 

14 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300