## NSN 5945-01-302-3299

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-302-3299

**Thread Class:** 

2a single mounting facility

**Overall Length:** 

Between 1.563 inches and 1.625 inches

**Overall Height:** 

Between 1.719 inches and 1.781 inches

Overall Width:

Between 1.000 inches and 1.062 inches

**Environmental Protection:** 

Hermetic

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.266 inches single mounting facility and 1.296 inches single mounting facility

**Fragility Factor:** 

Moderately rugged

**End Application:** 

Harpoon ctv p

**Winding Quantity:** 

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

1

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

3 threaded stud single mounting facility

Storage Type:

General purpose warehouse

**Cubic Measure:** 

3.074 cubic inches

**Thread Size:** 

0.138 inches single mounting facility

**Mounting Facility Pattern:** 

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:** 

2 pole, double throw, one position momentary

Time Delay:

2.00 seconds fixed operate time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.110 inches single mounting facility and 1.140 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-302-3299

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

9 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A03300