NSN 5945-01-302-3300

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-302-3300
Overall Length:
1.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Overall Height:
1.000 inches
Overall Width:

Unthreaded Mounting Hole Diameter:

0.150 inches single mounting facility

Fragility Factor:

1.718 inches

Moderately rugged

End Application:

Harpoon ctv p

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

320.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

1.933 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.015 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

NSN 5945-01-302-3300

Electromagnetic Relay - Page 2 of 2



Main	Contact	Maximum	Voltage	Rating	In	Volte:
viaiii	Contact	Waxiiiiuiii	vollaue	Nauiiu		voits.

200.0 ac and 28.0 dc

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300