## NSN 5945-01-302-3300

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-302-3300
Overall Length:
1.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Overall Height:
1.000 inches
Overall Width:

### **Unthreaded Mounting Hole Diameter:**

0.150 inches single mounting facility

**Fragility Factor:** 

1.718 inches

Moderately rugged

**End Application:** 

Harpoon ctv p

Winding Quantity:

1

#### **Purpose For Which Designed:**

General

**Coil Quantity:** 

1

#### Winding Dc Resistance Rating:

320.0 ohms single winding

**Duty Type:** 

Continuous

#### **Arc Quenching Method:**

Air

#### **Mounting Facility Type And Quantity:**

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

**Cubic Measure:** 

1.933 cubic inches

#### **Mounting Facility Pattern:**

In-line single mounting facility

#### **Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

Time Delay:

0.015 seconds fixed operate and release time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

# NSN 5945-01-302-3300

Electromagnetic Relay - Page 2 of 2



Main	Contact	<b>Maximum</b>	Voltage	Rating	In	Volte:
viaiii	Contact	Waxiiiiuiii	vollaue	Nauiiu		voits.

200.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

8 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300