## NSN 5945-01-303-4075

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-303-4075

### **Overall Length:**

1.531 inches

### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.182 inches single mounting facility and 1.192 inches single mounting facility

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.182 inches single mounting facility and 1.192 inches single mounting facility

### **Overall Height:**

2.087 inches

### **Overall Width:**

1.531 inches

#### **Environmental Protection:**

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.152 inches single mounting facility

#### **End Application:**

An/sqq-8 (v) 6 unit 132

### Frequency In Hertz:

400.0

### **Winding Quantity:**

### **Coil Quantity:**

1

### **Duty Type:**

Continuous

### **Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

### **Mounting Facility Pattern:**

Rectangular single mounting facility

### **Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, momentary action

### **Operating Current Rating And Type:**

25.0 amperes ac single winding

### **Nonpile-up Auxiliary Contact Arrangement:**

1 pole, double throw, one position momentary

### Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac motor load

### Main Contact Maximum Voltage Rating In Volts:

115.0 ac

### **Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes ac resistive load

### **Terminal Type And Quantity:**

4 threaded stud energizing element

# NSN 5945-01-303-4075

Electromagnetic Relay - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300