

View Online at <https://aerobasegroup.com/nsn/5945-01-303-4850>

**Thread Class:**

2a mounting facility stud

**Thread Direction:**

Right-hand mounting facility stud

**Body Style:**

Double ended actuator

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.240 inches and 1.260 inches

**Body Diameter:**

1.865 mils and 1.906 centimeters

**Body Height:**

Between 1.043 inches and 1.063 inches

**Maximum Operating Temp:**

125.0 degrees celsius

**Fragility Factor:**

Moderately rugged

**Actuator Diameter:**

Between 0.249 inches and 0.251 inches

**End Application:**

F16aircombfir

**Inclosure Type:**

Fully enclosed

**Magnetic Coil Quantity:**

1

**Electrical Resistance:**

4.30 ohms

**Duty Type:**

Intermittent

**Terminal Location:**

Circumference

**Voltage Rating In Volts:**

28.0 dc

**Mounting Facility Type And Quantity:**

2 threaded stud

**Current Rating:**

7.5 amperes

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32 mounting facility stud

**Actuator Stroke Type:**

Push

**Linear Force Delivered:**

16.00 pounds

**Power Takeoff Connection Type:**

Plain-drilled

**Energizing Stroke Maximum Length:**

0.135 inches

**Thread Size:**

0.164 inches mounting facility stud

**Mounting Facility Pattern:**

Two position in-line

**Thread Series Designator:**

Unc mounting facility stud

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A134a0